



ZODZ2.E75050 Positioning Devices - Component

[Page Bottom](#)
[Print-friendly version](#)
[Questions?](#)
[Previous Page](#)

Positioning Devices - Component

[See General Information for Positioning Devices - Component](#)

HUA WEI INDUSTRIAL CO LTD

E75050

25 YA TAN RD

SHI PAO VILLAGE

TA YA HSIANG

TAICHUNG HSIEN 428, TAIWAN

Cable ties, Cat. Nos. HW-045, -047, all colors, for use at temperature not exceeding 75 C . Cat. Nos. GT-80M, -90M, -100M, -120M, -160M, -200M, -140I, -200I, -300I, -370I, -190ST, -250ST, -300ST, -370ST, -390ST, -370HD, -830HD, GTR-140I, -190ST, -200ST, -300ST, -370ST, GTP-150I, -200ST, -110M, GTM-110M, -150I, -200ST, -300ST, -200HD, -300HD, -380HD, GTK-110M, -210M, -100M, -200M, -190ST, -270ST, -340ST, -300STL, -370STL, GTK2-190ST, -270ST, -340ST, -220STL, -300STL, -370STL, GTK3-190ST, -270ST, -340ST, -220STL, -300STL, -370STL, white color only, for use at temperature not exceeding 75 C.

Cable ties, Cat. Nos. GT-80M, -90M, -100M, -120M, -160M, -200M, -140I, -200I, -300I, -370I, -190ST, -250ST, -300ST, -370ST, -390ST, GT-370HD, GTR-140I, -190ST, -200ST, -300ST, -370ST, GTP-150I, -200ST, -110M, GTM-110M, -150I, -200ST, -300ST, -200HD, -300HD, -380HD, GTK-110M, -210M, -100M, -200M, -190ST, -270ST, -340ST, -300STL, -370STL, GTK2-190ST, -270ST, -340ST, -220STL, -300STL, -370STL, GTK3-190ST, -270ST, -340ST, -220STL, -300STL, -370STL, black color only, for use at temperatures not exceeding 85 C.

Cable ties, Cat. Nos. GT-120I, -140M, -150HD, -150I, -120ST, -160ST, -180I, -200HD, -200ST, -230EHD, -240LT, -250HD, -250I, -280ST, -300HD, -430HD, -430ST, -450ST, -480EHD, -490LT, -530HD, -530ST, -580EHD, -590LT, -630HD, -710HD, -730EHD, -740LT, -780HD, -880EHD, -920HD, -1020HD, -1220HD, -1030EHD, GTK-220STL, all colors, for use at temperatures not exceeding 85 C.

Cable tie, Cat. No. GTP-130I, all colors, for use at temperatures not exceeding 85 C.

Hole mounted cable ties, Cat. Nos. GTP-130ST, -170ST, -190ST, all colors, for use at temperatures not exceeding 85 C.

Releasable Cable tie, Cat. No. GTRP-130I, all color, for use at temperatures not exceeding 85 C.

Cable ties, Cat. Nos. GT-80MH, -90MH, -100MH, -120MH, -140MH, -150MH, -160MH, -200MH, -250MH, -300MH, -120IH, -140IH, -150IH, -180IH, -200IH, -215IH, -250IH, -300IH, -370IH, -

120STH, -150STH, 160STH, -190STH, -200STH, -216STH, -250STH, -266STH, -280STH, -300STH, -370STH, -390STH, 430STH, -50STH, -530STH, -550STH, -635STH, -685STH, -730STH2, -730STH, -830STH, -150HDH, -200HDH, -240HDH, -250HDH, -280HDH, -300HDH, -370HDH, -430HDH, -450HDH, -530HDH, -630HDH, -710HDH, 780HDH, -830HDH, -920HDH, -920HDH2, -1020HDH, -1070HDH, -1220HDH, -1530HDH, GTE-100MH, -160MH, -200MH, -140IH, -200IH, -300IH, -370IH, -160STH, -190STH, -280STH, -300STH, -370STH, -200HDH, -250HDH, -300HDH, -370HDH, -430HDH, -450HDH, -530HDH, -230EHDH, -290EHDH, -380EHDH, -480EHDH, -580EHDH, -730EHDH, -880EHDH, -1030EHDH, all color, for use at temperatures not exceeding 120C.

Cable ties with integral tail holder, Cat. Nos. GT-240LTH, -300LTH, -415LTH, -490LTH, -590LTH, -740LTH, -890LTH, -1040LTH, all color, for use at temperatures not exceeding 120C.

Cable ties, releasable, with integral tail holder, Cat. Nos. GTR-240LTH, -300LTH, -415LTH, -490LTH, -590LTH, -740LTH, -890LTH, -1040LTH, all color, for use at temperatures not exceeding 120C.

Cable ties, short catch ridge length, Cat. Nos. GT-300IAH, -600IAH, -800IAH, all color, for use at temperatures not exceeding 120C.

Cable ties, double ratchet, Cat. Nos. GTB-200STH, -300STH, -370STH, all color, for use at temperatures not exceeding 120C.

Bead type tie, Cat. No. GTB100H, all color, for use at temperatures not exceeding 120C.

Bead type tie, hole mounted, Cat. No. GTMB-90, all color, for use at temperatures not exceeding 120C.

Cable tie, releasable, Cat. No. GTER-370STH, all color, for use at temperatures not exceeding 120C.

Cable ties, marker throat, Cat. Nos. GTK-110MAH, -100MH, -110MH, -200MH, -210MH, -190STH, -220STH, -270STH, -300STH, -370STH, -270STLH, -300STLH, -370STLH, all color, for use at temperatures not exceeding 120C.

Cable ties, double marker, Cat. Nos. GTK2-220STH, -270STH, -300STH, -370STH, -270STLH, -220STLH, -300STLH, -370STLH, all color, for use at temperatures not exceeding 120C.

Cable ties, triple marker, Cat. Nos. GTK3-220STH, -270STH, -300STH, -370STH, -220STLH, -270STLH, -300STLH, -370STLH, all color, for use at temperatures not exceeding 120C.

Cable ties, Screw mount, Cat. Nos. GTM-110MH, -150I, -200STH, -300STH, -370STH, -200HDH, -300HDH, -380HDH, all color, for use at temperatures not exceeding 120C.

Cable ties, hole mounted, Cat. Nos. GTP-130IH, -150IH, -110MH, -130STH, -170STH, -190STH, -200STH, all color, for use at temperatures not exceeding 120C.

Cable ties, releasable, Cat. Nos. GTR-140IH, -200STH, -300STH, -370STH, -430STH, -450STH, -530STH, -290EHDH, -380EHDH, -480EHDH, -580EHDH, -730EHDH, -880EHDH, -1030EHDH, all color, for use at temperatures not exceeding 120C.

Cable ties, single tooth with release handle, Cat. Nos. GTRN-100HDH, -120HDH, -150HDH, -200HDH, -250HDH, -300HDH, -370HDH, all color, for use at temperatures not exceeding 120C.

Cable tie, hole mounted, releasable, Cat. No. GTRP-130IH, all color, for use at temperatures not exceeding 120C.

Cable ties#, Cat. Nos. GT-80MHUV, -90MHUV, -100MUV, -120MUV, -140MUV, -150MUV, -160MUV, -200MUV, -250MUV, -300MUV, -120IUV, -140IUV, -150IUV, -180IUV, -200IUV, -215IUV, -250IUV, -300IUV, -370IUV, -120STUV, -150STUV, 160STUV, -190STUV, -200STUV, -216STUV, -250STUV, -266STUV, -280STUV, -300STUV, -370STUV, -390STUV, 430STUV, -50STUV, -530STUV, -550STUV, -635STUV, -685STUV, -730STUV2, -730STUV, -830STUV, -150HDUV, -200HDUV, -240HDUV, -250HDUV, -280HDUV, -300HDUV, -370HDUV, -430HDUV, -450HDUV, -530HDUV, -630HDUV, -710HDUV, 780HDUV, -830HDUV, -920HDUV, -920HDUV2, -1020HDUV, -1070HDUV, -1220HDUV, -1530HDUV, GTE-100MHUV, -160MUV, -200MUV, -140IUV, -200IUV, -300IUV, -370IUV, -160STUV, -190STUV, -280STUV, -300STUV, -370STUV, -200HDUV, -250HDUV, -300HDUV, -370HDUV, -430HDUV, -450HDUV, -530HDUV, -230EHDHUV, -290EHDHUV, -380EHDHUV, -480EHDHUV, -580EHDHUV, -730EHDHUV, -880EHDHUV, -1030EHDHUV, for use at temperatures not exceeding 85C.

Cable ties with integral tail holder, Cat. Nos. GT-240LTHUV, -300LTHUV, -415LTHUV, -490LTHUV, -590LTHUV, -740LTHUV, -890LTHUV -1040LTHUV, black color, for use at temperatures not exceeding 85C.

Cable ties, releasable, with integral tail holder, Cat. Nos. GTR-240LTHUV, -300LTHUV, -415LTHUV, -490LTHUV, -590LTHUV, -740LTHUV, -890LTHUV, -1040LTHUV, black color, for use at temperatures not exceeding 85C.

Cable ties, short catch ridge length#, Cat. Nos. GT-300IAUV, -600IAUV, -800IAUV, for use at temperatures not exceeding 85C.

Cable ties, double ratchet #, Cat. Nos. GTB-200STUV, -300STUV, -370STUV, for use at temperatures not exceeding 85C.

Bead type tie #, Cat. No. GTB100UV, for use at temperatures not exceeding 85C.

Bead type tie, hole mounted #, Cat. No. GTMB-90UV, for use at temperatures not exceeding 85C.

Cable tie, releasable #, Cat. No. GTER-370STUV, for use at temperatures not exceeding 85C.

Cable ties, marker throat #, Cat. Nos. GTK-110MAUV, -100MUV, -110MUV, -200MUV, -210MUV, -190STUV, -220STUV, -270STUV, -300STUV, -370STUV, -270STLUV, -300STLUV, -370STLUV, for use at temperatures not exceeding 85C.

Cable ties, double marker #, Cat. Nos. GTK2-220STUV, -270STUV, -300STUV, -370STUV, -270STLUV, -220STLUV, -300STLUV, -370STLUV, for use at temperatures not exceeding 85C.

Cable ties, triple marker #, Cat. Nos. GTK3-220STUV, -270STUV, -300STUV, -370STUV, -220STLUV, -270STLUV, -300STLUV, -370STLUV, for use at temperatures not exceeding 85C.

Cable ties, Screw mount #, Cat. Nos. GTM-110MUV, -150IUV, -200STUV, -300STUV, -370STUV, -200HDUV, -300HDUV, -380HDUV, for use at temperatures not exceeding 85C.

(#) - Black color only: Manufactured from a material which has been subjected to one or more of the following tests: Ultraviolet Light, Water Exposure or Immersion in accordance with UL746C, where the acceptability for outdoor use is to be determined by UL.

Marking: Company name or "E75050" "For use within enclosures only", and catalog designation on the product or smallest unit package, box or container or may be molded on the device. Maximum fill diameter, maximum and minimum panel thickness, hole diameters and screw sizes on smallest unit package, box or container or in the installation instructions shipped with the devices.

Last Updated on 2005-01-27

[Page Top](#)

[Notice of Disclaimer](#)

[Questions?](#)

[Previous Page](#)

[UL Listed and Classified Products](#)

[UL Recognized Components](#)

[Products Certified for Canada](#)

This page and all contents are Copyright © 2005 by Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2005 Underwriters Laboratories Inc.®"